

THE MOST RESILIENT SOLUTION

Since 1895, NIEDNER has been redefining the firefighting industry by creating lighter, more versatile lay-flat hoses to overcome the challenges firefighters face. What makes firefighters around the globe trust NIEDNER's ALTRA FIRE solutions is first and foremost the high quality and resiliency of the products. Our hoses are engineered to stand up under the most demanding applications, including intense heat and abrasion.

COMBAT LARGE SCALE FIRES

A durable attack or high-rise pack hose with a service test pressure rating of 400 PSIG (2800 kPa), perfect for fire departments on the go. This 100% polyester double-jacket fire hose is lined with TPU elastomer and built for ruggedness, while remaining lightweight and compact. ALTRA 2000 has superior flow characteristics. The tight weave of the outer jacket resists snags, cuts, punctures and abrasion. The ENCAP™ treatment improves durability, reduces water absorption up to 40%, increases chemical resistance and allows for color options.

HIGHEST LEVEL OF QUALITY

NIEDNER maintains the highest levels of quality in the design, manufacturing, and testing of all our products. As a result, our solutions exceed the recognized international standards.

UNIQUE SERVICES

Our solutions have many advantages, including our unique services and our engineering support, which is second to none.



Highly safe hose



Corrosion and maintenance-free



Short lead-times and quick to install



Reusable



Standard lengths: 50/100 feet



Increased resiliency



Commitment to the environment

Formally known as ULTRA2000

NIEDNER-ALTRA.COM ALTRA ATTACK



FEATURES

- Abrasion and puncture resistant
- Kink resistant
- Ozone, age, mildew and bacteria resistant

ADVANTAGES

- Lightweight and compact
- Reduced water absorption up to 40%

DESIGN

- Made of 100% polyester
- Lined with TPU elastomer
- ENCAP™ treatment

OUR PRODUCT LINE CERTIFICATIONS

NIEDNER's solutions are certified by accredited independent institutes







TECHNICAL DATA

Diameter		Weight				Flat width		Thickness		Coil Diam.		Internal		Coupling		Pressure	
Inches	Spec	50 ft., w/alum cplgs		100 ft., w/alum cplgs		All lengths		Layflat		50 ft., w/couplings		Diameter		Bowl size		Service test	
(mm)	#	lb	kg	lb	kg	in	cm	in	cm	in	cm	in	mm	in	mm	PSI	kPA
1 1/2" (38mm)	4115	14	6.35	26	11.79	2.875	7.30	0.25	0.64	20	50.8	1 11/16	43	1-15/16	49.2	400	2800
1 3/4" (45mm)	4117	16	7.26	30	13.61	3.125	7.94	0.28	0.71	20	50.8	1 13/16	46	2-1/16	52.4	400	2800
2" (51mm)	4120	19	8.62	37	16.78	3.375	8.57	0.28	0.71	20	50.8	2-1/16	52	2 5/16	58.7	400	2800
2 1/2" (64mm)	4125	24	10.89	46	20.87	4.5	11.43	0.28	0.71	21	53.34	2-3/4	70	3"	76.2	400	2800

AVAILABLE COLORS: White, Green, Red, Orange, Blue, Beige-Tan, Purple and Yellow